

YOUR  
SMART  
ENERGY



# SMILE5

RESIDENTIAL SERIES

## POWER

5 kW Inverter

## CAPACITY

10.1 / 13.3 kWh

Battery Modular

Expandable to 80 kWh



reddot design award 2018



product design award 2018



5kW single phase hybrid inverter

Fast response

UPS ability

24/7 Monitoring

- S**elf sufficient
- M**odular battery
- I**ntelligent control
- L**ong lifespan
- E**ssential load protected
- 5** kW system



# SMILE5



Model		SMILE5	
<b>System Specification</b>			
Rated Output Power	5000 W		
Rated Output Apparent Power	5000 VA		
Capacity Range	10.1 ~ 60.6 kWh(96% DoD)	13.3 ~ 80 kWh(100% DoD)	
Usable Capacity Range	9.7 ~ 58.1 kWh	13.3 ~ 80 kWh	
Battery Chemistry	LFP (LiFePO4)		
IP Protection	IP65		
Warranty	5 Year Product Warranty, 10 Year Battery Warranty		

<b>Inverter Technical Specification</b>			
Model	SMILE5-INV	Rated Output Apparent Power (Backup Port)	5000 VA
Coupling	Hybrid	Max. AC input Power (Grid Port)	7500 W
Max. PV Input Power	7500 W	Rated Output Current (Grid Port)	21.7 A
Max. PV Input Current	15 A / 15 A	Max. AC Output Current (Grid Port)	21.7 A
Max. PV Input Voltage	550 V	Rated Output Current (Backup Port)	21.7 A
Start-up input voltage	90 V	Max. AC Output Current (Backup Port)	21.7 A
Rated PV Input Voltage	360 V	Max Inverter Efficiency	96.50%
MPPT Number/Max. Input Strings Number Per MPPT	2/1	Backup	UPS
MPPT Voltage Range	70 ~ 540 V	Communication	Ethernet / WIFI
Max. PV Short-circuit Current	18 A / 18 A	Humidity	0 ~ 90% (No Condensing)
Max. Charging/Discharging Current	100 A	Dimension (W x D x H)	610 x 210 x 627 mm
Max. Charging/Discharging Power	5000 W	Weight	27.7 kg
Rated Frequency	50 / 60 Hz	Safety	IEC 62109
Rated Voltage	230 V	EMC	EN 61000-6-1 / EN 61000-6-3
Rated Output Apparent Power (Grid Port)	5000 VA	Grid Regulation	AS 4777.2

<b>Battery Technical Specification</b>		
Module Model	SMILE-BAT-10.1P	SMILE-BAT-13.3P
Module Capacity	10.1 kWh	13.3 kWh
Module Nominal Voltage	48 V	48 V
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
Max. Modules in Parallel	6	6**
Max. Charging / Discharging Current	100 A	100 A
Cycle Life	8000***	8000***

\* When the ambient temperature is too low or too high, the performance of battery may be limited.  
 \*\* ≥2 needs to install expansion pack  
 \*\*\* Under specific test conditions



#### Alpha ESS Co., Ltd.

+86 513 8060 6891  
 info@alpha-ess.com  
 www.alphaess.com  
 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

#### Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609  
 info@alpha-ess.com  
 www.alphaess.com  
 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

#### Alpha ESS Europe GmbH

+49 610 3459 1601  
 europe@alpha-ess.de  
 www.alphaess.de  
 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

#### Alpha ESS Australia Pty. Ltd.

+61 402 500 520  
 info@alpha-ess.com  
 www.alphaess.com

#### Alpha ESS Italy S.r.l.

+39 339 462 4288  
 info@alpha-ess.it  
 www.alphaess.com  
 Via Don Minzoni, 17, Calenzano Firenze 50041

#### Alpha ESS UK Ltd.

+44 145 354 5222  
 info@alpha-ess.com  
 Drake House, Long Street, Dursley, gl11 4hh

#### Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126  
 Singapore@alpha-ess.com  
 2 Corporation Road #01-06A Corporation Place Singapore 618494

#### Alpha ESS USA, Inc.

+1 408 368 7828  
 usa@alpha-ess.com  
 Unit 5, 2180 S Ivanhoe St, Denver, CO 80222

#### Alpha ESS Korea Co., Ltd.

info@alpha-ess.com  
 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea