

Up to 430 watt

WST-NGX-D3

N-Type Bifacial Glass-Glass Series

Higher yield panel design for commercial and residential owners



PERFORMANCE WARRANTY




COMPLIMENTARY INSURANCE




www.winaico.com.au

DIMENSIONS




PACKAGING



MECHANICAL DATA WINAICO WST-NGX-D3 SERIES

Cell	Monocrystalline, N-type, bifacial
Quantity and wiring of cells	108 (6 strings x 18 cells)
Bifaciality	Up to 80 %
Dimensions	1,722 x 1,134 x 35 mm (67.80 x 44.65 x 1.38 in)
Weight	24 kg (52.9 lbs)
Front-side glass	2.0 mm, tempered solar glass with anti-reflective coating
Back-side glass	2.0 mm, tempered solar glass, partially white printed
Encapsulant material	POE
Frame	Black anodised aluminium
Junction box	IP68, 3 bypass diodes
Connector type	MC4-EVO2A IP68
Cable length (IEC/UL)	Cable 2 x 1.2 m (47.24 in) / 4 mm ²
Fire safety class	C

WINAICO PERFORMANCE GUARANTEE



Operating conditions

Operating temperature	
Maximum system voltage IEC/UL	
Maximum series fuse	
Maximum design load (push/pull)	
Maximum test load (push/pull)	
Nominal module operating temperature NMOT	
Temperature coefficient of P_{MAX}	
Temperature coefficient of V_{OC}	
Temperature coefficient of I_{SC}	
Certifications	

WINAICO WST-NGX-D3

Operating temperature	-40 °C to +85 °C / -40 °F to +185 °F
Maximum system voltage IEC/UL	1,500V/1,500V
Maximum series fuse	30 A
Maximum design load (push/pull)	5,400 Pa/2,400 Pa
Maximum test load (push/pull)	8,100 Pa/3,600 Pa
Nominal module operating temperature NMOT	42 ± 2 °C
Temperature coefficient of P_{MAX}	-0.30%/°C
Temperature coefficient of V_{OC}	-0.25%/°C
Temperature coefficient of I_{SC}	0.045%/°C
Certifications	IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016

Electrical data (STC)¹

Nominal performance	P_{MAX}	
Voltage at maximum performance	V_{MP}	
Current at maximum performance	I_{MP}	
Open circuit voltage	V_{OC}	
Short circuit current	I_{SC}	
Module efficiency		
Bifacial gain ³	10 % Pmpp	
	15 % Pmpp	
	20 % Pmpp	
Power tolerance		

WST-430NGX-D3

Nominal performance	P_{MAX}	430	Wp
Voltage at maximum performance	V_{MP}	32.68	V
Current at maximum performance	I_{MP}	13.16	A
Open circuit voltage	V_{OC}	38.60	V
Short circuit current	I_{SC}	13.80	A
Module efficiency		22.02	%
Bifacial gain ³	10 % Pmpp	473 (+43)	W
	15 % Pmpp	494 (+64)	W
	20 % Pmpp	516 (+86)	W
Power tolerance		-0/+5	W

Electrical data (NMOT)²

Nominal performance	P_{MAX}	
Voltage at maximum performance	V_{MP}	
Current at maximum performance	I_{MP}	
Open circuit voltage	V_{OC}	
Short circuit current	I_{SC}	

WST-430NGX-D3

Nominal performance	P_{MAX}	322	Wp
Voltage at maximum performance	V_{MP}	30.51	V
Current at maximum performance	I_{MP}	10.56	A
Open circuit voltage	V_{OC}	36.52	V
Short circuit current	I_{SC}	11.12	A

1. Electrical data applies under standard test conditions (STC): solar radiation 1,000 W/m² with light spectrum AM 1.5, with cell temperature 25 °C. Measurement tolerance of P_{MAX} at STC: ±3%. Accuracy of other electrical data: ±10%.
2. Electrical data applies under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20 °C, wind speed 1 m/s.
3. The additional power gain from the rear side depends on the irradiance conditions at the installation site and the mounting situation.



WINAICO Australia Pty Ltd
 Tel + 61 2 8091 2771
 australia@winaico.com
 https://www.winaico.com.au/
 3/393 George Street, Sydney NSW 2000, Australia



WINAICO is a trademark of
 Win Win Precision Technology Co., Ltd.

Win Win Precision Technology Co., Ltd

Tel + 886 3 568 8699 · info@w-win.com.tw
 www.wwpt.com.tw · www.winaico.com
 4F., No. 180, Sec. 2, Gongdao 5th Rd., East Dist.,
 Hsinchu City 300, Taiwan R.O.C.
 Made in China